



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 IHP
Device short name	IHP
Product or component type	Programmable digital time switch
Device application	Building
Battery type	Lithium
Number of channels	1
Language	English Swedish Danish French Norwegian Dutch Finnish
Colour tint	White (RAL 9003)

Complementary

Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V[Sapce](+/- 10 %) AC 50/60 Hz
Cycle duration	24 hours + 7 days
Maximum number of switchings	28
Minimum interval duration	1 min
Accuracy	+/- 1 s/day 20 °C
Display type	Backlit LCD
Battery life	5 yr
Backup time	3 years time and program saving
Mounting support	DIN rail
9 mm pitches	2
Function available	Automatic winter/summer time changeover
Connections - terminals	Screw terminals

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	18 mm
Height	85 mm
Depth	66 mm
Function	None
Absence for holidays	No
Time changeover	Automatic
Updated by	None
Compatibility code	IHP

Environment

IP degree of protection	IP20 B
Ambient air temperature for operation	-10...50 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------