



Main

Range of product	Multi 9
Range	Multi 9
Product name	Multi 9 CDS
Product or component type	Load-shedding contactor
Device short name	CDSc
Number of channels	4
Control and monitoring type	Cascade
Poles description	1P

Complementary

Setting	90 45 20 60 15 75 25 50 10 30 5 40
Power consumption in VA	<= 4 VA
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz
Rated current	Non-priority circuit : 15 A Priority circuit : adjustable from 5 to 90 A
Local signalling	4 LEDs yellow : load-shedding indication
Mounting support	Wall mounted 35 mm symmetrical DIN rail Panel mounting
9 mm pitches	16
Connections - terminals	Non-priority circuit : screw terminal 2.5...10 mm ² Priority circuit : screw terminal 4...50 mm ²
IP degree of protection	IP20 IP40
Height	77 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	145 mm
Depth	67 mm
Product weight	0.6 kg
Colour	Grey RAL 7035
Compatibility code	CDS <i>c</i>

Environment

Standards	NF C 61-750 EN 50081-1 EN 50081-2
Ambient air temperature for operation	-5...55 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status

END-OF-SALE NOTICE