



Main

Range of product	Multi 9
Range	Multi 9
Product name	Multi 9 CDS
Product or component type	Load-shedding contactor
Device short name	CDS
Number of channels	3
Control and monitoring type	Independant phase control
Poles description	3P

Complementary

Setting	50 15 40 90 70 20 10 25 80 5 30 60
Power consumption in VA	<= 12 VA
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz
Rated current	Non-priority circuit : 15 A Priority circuit : adjustable from 5 to 90 A
Local signalling	3 LEDs yellow : load-shedding indication
Mounting support	Panel mounting Wall mounted 35 mm symmetrical DIN rail
9 mm pitches	16
Connections - terminals	Non-priority circuit : screw terminal 2.5...10 mm ² Priority circuit : screw terminal 4...50 mm ²
IP degree of protection	IP20 IP40
Height	77 mm

Width	145 mm
Depth	67 mm
Product weight	0.5 kg
Colour	Grey RAL 7035
Compatibility code	CDS
Market segment	Small commercial

Environment

Standards	NF C 61-750 EN 50081-1 EN 50081-2
Ambient air temperature for operation	-5...55 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------