



### Main

Range of product	CT
Product or component type	Contacteur
Device short name	CT
Device application	Control circuit
Poles description	4P
[Ie] rated operational current	63 A AC-7A
Pole contact composition	3 NO + 1 NC
Network type	AC
Utilisation category	AC-1 conforming to IEC 60947-4 AC-3 conforming to IEC 60947-4 AC-7A conforming to IEC 61095 AC-7B conforming to IEC 61095
Control type	Remote control
[Uc] control circuit voltage	220/240 V AC 50 Hz

### Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	400 V AC 50 Hz
Maximum power	13.8 W 400 V AC
Control signal type	Maintained
Local signalling	Color indicator
Hold-in power consumption in VA	6.5 VA
Inrush power in VA	53 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical durability	200000 cycles AC 50/60 Hz conforming to EN 60947-4-1 200000 cycles AC 50/60 Hz conforming to EN 61095 200000 cycles AC 50/60 Hz conforming to IEC 1095

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	Control circuit : 2 tunnel type terminals 2.5 mm <sup>2</sup> for flexible cable(s) Control circuit : 2 tunnel type terminals 1.5 mm <sup>2</sup> for rigid cable(s) Power circuit : 2 tunnel type terminals 10 mm <sup>2</sup> for flexible cable(s) Power circuit : 1 tunnel type terminals 25 mm <sup>2</sup> for rigid cable(s)
Product compatibility	Auxiliary contact Interference filter Mixed control: impulse/latched Time delay
Compatibility code	CT

## Environment

Standards	EN 61095 IEC 1095 EN 60947-4-1
Product certifications	IMQ GOST VDE CCC CEBEC
Noise level	30 dB
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...60 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------