



### Main

Range	DuoLine
Product or component type	Distribution block
Device short name	Distri'cl'ic XE
Accessory / separate part category	Connection accessory
Lines description	1L + N
Total number of 18 mm modules	5

### Complementary

Number of ways	5 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm
Connector type	Plug-in
Distance between way	18 mm
Incomer device	ID'cl'ic XE R'cl'ic XE
Insulation	Insulated
[Ie] rated operational current	63 A ( 40 °C )
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	250 V AC
Mounting mode	Horizontal
Mounting location	Top on plug in
9 mm pitches	10
Width	90 mm
Connections - terminals	Screw terminals 16 mm <sup>2</sup>
Range compatibility	Pragma Opale DuoLine D'cl'ic XE DuoLine ID'cl'ic XE DuoLine R'cl'ic XE

**Offer Sustainability**

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0643 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------