



Main

Range	DuoLine
Product or component type	Distribution block
Device short name	Distri'cl'ic XE
Accessory / separate part category	Connection accessory
Lines description	1L + N
Total number of 18 mm modules	18

Complementary

Number of ways	18 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm
Connector type	Plug-in
Distance between way	18 mm
Incomer device	ID'cl'ic XE R'cl'ic XE
Insulation	Insulated
[Ie] rated operational current	63 A (40 °C)
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	250 V AC
Mounting mode	Horizontal
Mounting location	Top on plug in
9 mm pitches	36
Width	324 mm
Connections - terminals	Screw terminals 16 mm ²
Range compatibility	Opale Pragma DuoLine D'cl'ic XE DuoLine ID'cl'ic XE DuoLine R'cl'ic XE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0643 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------