



### Main

Range of product	DuoLine
Range	DuoLine
Product name	DuoLine CM'clic
Product or component type	Selector switch
Device short name	CM'clic
Device application	Electrical circuit control
Contacts type and composition	1 NO + 1 NC
[Ue] rated operational voltage	250 V AC
Standards	EN 60947-5-1 EN 60669-1
Quality labels	NF

### Complementary

[Ie] rated operational current	20 A
Control type	Toggle 2 positions
Marking	0 - 1
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Upside : Bar'clic
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	75 mm
Electrical durability	AC-22 : 30000 cycles
Connections - terminals	Staggered tunnel terminal 2 cable(s) <= 2.5 mm <sup>2</sup> flexible with cable end Staggered tunnel terminal 2 cable(s) <= 2.5 mm <sup>2</sup> flexible without cable end Staggered tunnel terminal 2 cable(s) <= 2.5 mm <sup>2</sup> rigid with cable end Staggered tunnel terminal 2 cable(s) <= 2.5 mm <sup>2</sup> rigid without cable end
Compatibility code	CM_CLIC

16198

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---