



Main

Range of product	DuoLine
Range	DuoLine
Product name	DuoLine IH' clic
Device short name	IH' clic
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Complementary

Device application	Residential
Load type	10 parallel-corrected fluorescent tube, (58 W) 15 parallel-corrected fluorescent tube, (40 W) 230 V AC halogen lamp, (1000 W) 230 V AC incandescent lamp, (1000 W) 3 parallel-corrected fluorescent tube, (100 W) 7 fluocompact lamp, (11 W) 7 fluocompact lamp, (15 W) 7 fluocompact lamp, (20 W) 7 fluocompact lamp, (7 W)
Cycle duration	24 h
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	48 on - 48 off
Minimum interval duration	15 min
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	(+/- 10 %) 230 V AC 50/60 Hz
Backup time	100 h time and program saving
Mounting support	DIN rail
9 mm pitches	2
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP degree of protection	IP20 B
Width	18 mm
Product weight	0.095 kg
Function	None
Absence for holidays	No
Time changeover	Manual
Updated by	None
Compatibility code	IH_CLIC

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	Terminals : IP20 B

Contractual warranty

Warranty period	18 months
-----------------	-----------