



### Main

Range of product	PRD
Range	Multi 9
Product name	Multi 9 PRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	PRD40r
Device application	Distribution
Poles description	3P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz 400 V (+/- 10 %) AC 50/60 Hz
Nominal discharge current	Common mode : 15 kA L/PE
Maximum discharge current	Common mode : 40 kA L/PE
[Uc] maximum continuous operating voltage	Common mode : 460 V L/PE
[Up] voltage protection level	1.9 kV type 2 common mode L/PE
Disconnecter device type	Associated circuit breaker 40 A - Icu 10 kA Associated circuit breaker 40 A - Icu 15 kA Associated circuit breaker 40 A - Icu 25 kA
Local signalling	Flag color: white/red
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting support	DIN rail
9 mm pitches	8
Height	81 mm
Width	72 mm
Depth	69 mm
Colour	Grey ( RAL 7035 )
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal, downside 2.5...35 mm <sup>2</sup> Tunnel type terminal, upside 2.5...35 mm <sup>2</sup>
Tightening torque	2.5 N.m
Compatibility code	PRD40r

## Environment

IP degree of protection	On front face : IP40 conforming to IEC 60529 On terminal : IP20 conforming to IEC 60529
IK degree of protection	IK03 conforming to IEC 62262
Relative humidity	5...90 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------