

Product data sheet

Characteristics

16940

auxiliary contact - 1 NC + 1 OC - 380..415 V - 6 A
- for RCCB



Main

Range	Multi 9
Range of product	ID RCCB
Product or component type	OC contact
Device short name	OFSP
Signal contacts composition	1 C/O 1 NC
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC

Complementary

Mounting mode	Fixed
Mounting support	DIN rail
Connections - terminals	Tunnel type terminal 2 cable(s) 1...1.5 mm ² flexible Tunnel type terminal 2 cable(s) 1...1.5 mm ² rigid
Tightening torque	0.8 N.m
Product compatibility	ID
Market segment	Small commercial

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0630 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
