



### Main

Range of product	Modicon Momentum automation platform
Accessory / separate part designation	Branch interface
Accessory / separate part type	Interface
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Interbus communication adaptor
Communication port protocol	Interbus generation SUP1 2

### Complementary

[Us] rated supply voltage	24 V DC
Output current limits	0.2...2 A
Power dissipation in W	2.5 W
Current consumption	100 mA
Electrical connection	1 RS485 connector RJ45 for incoming remote bus 1 RS485 connector RJ45 for outgoing remote bus 1 terminal block 8
Local signalling	1 LED green remote bus check (RC) 1 LED green bus active (BA) 1 LED green local remote bus branch disabled (LD) 1 LED green ready for operation (ready) 1 LED green relay output (REL) 1 LED red remote bus branch error (E) 1 LED red remote bus disabled (RD)
Product weight	0.015 kg

### Environment

Standards	DIN 19258
-----------	-----------

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1015 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---