



### Main

|                           |   |
|---------------------------|---|
| Range of product          | C60   |
| Range                     | Multi 9   |
| Product name              | Multi 9 C60   |
| Product or component type | Miniature circuit-breaker   |
| Device short name         | C60 UL1077  |
| Device application        | Distribution  |
| Poles description         | 2P  |
| Number of protected poles | 2   |
| Neutral position          | Left  |
| [In] rated current        | 7 A at 25 °C  |
| Network type              | AC<br>DC  |
| Trip unit technology      | Thermal-magnetic  |
| Curve code                | D   |
| Breaking capacity code    | N   |
| Breaking capacity         | AIR 10 kA at 240 V AC conforming to UL 1077<br>AIR 10 kA at 240 V AC conforming to CSA C22.2 No 235<br>AIR 10 kA at 125 V DC conforming to UL 1077<br>AIR 10 kA at 125 V DC conforming to CSA C22.2 No 235<br>Icu 6 kA at 440 V AC conforming to EN/IEC 60947-2<br>Icu 10 kA at 415 V AC conforming to EN/IEC 60947-2<br>Icu 20 kA at 240 V AC conforming to EN/IEC 60947-2<br>Icu 6 kA at 440 V AC conforming to GB 14048.2<br>Icu 10 kA at 415 V AC conforming to GB 14048.2<br>Icu 20 kA at 240 V AC conforming to GB 14048.2<br>AIR 5 kA at 480Y/277 V AC conforming to UL 1077<br>AIR 5 kA at 480Y/277 V AC conforming to CSA C22.2 No 235<br>Icu 10 kA at 125 V DC conforming to EN/IEC 60947-2<br>Icu 10 kA at 125 V DC conforming to GB 14048.2 |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

|  |   |
|--|---|
| Network frequency                      | 50/60 Hz  |
| [Ue] rated operational voltage         | 125 V DC<br>240 V AC<br>440 V AC<br>415 V AC  |
| Magnetic tripping limit                | 12 x In +/- 20% AC<br>17 x In +/- 20% DC  |
| Limitation class                       | 3 conforming to EN/IEC 60947-2  |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2   |
| Contact position indicator             | Yes   |
| Control type                           | Toggle  |
| Local signalling                       | ON/OFF indication   |
| Mounting mode                          | Clip-on   |
| Mounting support                       | DIN rail  |
| Connection pitch                       | 18 mm Between phases  |
| 9 mm pitches                           | 4   |
| Height                                 | 81 mm   |
| Width                                  | 36 mm   |
| Depth                                  | 73 mm   |
| Product weight                         | 0.22 kg   |
| Colour                                 | Grey  |
| Mechanical durability                  | 20000 cycles  |
| Electrical durability                  | 10000 cycles  |
| Provision for padlocking               | Padlockable   |
| Connections - terminals                | Tunnel type terminal, top or bottom rigid wire(s) 2.5...25 mm <sup>2</sup> max (AWG 14...AWG 4) |
| Wire stripping length                  | 14 mm top or bottom   |
| Tightening torque                      | 2.5 N.m top or bottom   |
| Compatibility code                     | C60_UL1077  |

## Environment


|                                       |  |
|---------------------------------------|--|
| Standards                             | UL 1077<br>GB 14048.2<br>EN/IEC 60947-2<br>CSA C22.2 No 235                        |
| Product certifications                | CSA<br>CCC<br>IEC<br>UR  |
| IP degree of protection               | IP40 for modular enclosure conforming to IEC 60529<br>IP20 conforming to IEC 60529 |
| Pollution degree                      | 3 conforming to EN/IEC 60947-2   |
| Overvoltage category                  | IV   |
| Tropicalisation                       | 2 conforming to IEC 60068-1  |
| Relative humidity                     | 95 % 55 °C   |
| Operating altitude                    | 2000 m   |
| Ambient air temperature for operation | -30...70 °C  |
| Ambient air temperature for storage   | -40...80 °C  |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0627 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                    | Reference not containing SVHC above the threshold   |

Reference not containing SVHC above the threshold

---

|                                  |  |
|----------------------------------|--|
| Product environmental profile    | Available<br> Product environmental |
| Product end of life instructions | Need no specific recycling operations  |

---

### Contractual warranty

---

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

---

17455