



Main

Range of product	V
Product or component type	Modular pilot lighth
Device short name	V
[Us] rated supply voltage	110...230 V AC 50/60 Hz

Complementary

Flashing frequency	2 Hz
Local signalling	LED red, service life 100000 h of constant lighting efficiency (consumption 0.3 W)
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside : ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Auxiliary connection terminal	Tunnel type terminal 2 cable(s) flexible 2.5 mm ² with cable end Tunnel type terminal 2 cable(s) flexible 2.5 mm ² without cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm ² with cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm ² without cable end
Compatibility code	V

Environment

Standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2

Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...100 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0917 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------