



### Main

Range of product	V
Product or component type	Modular pilot lighth
Device short name	V
[Us] rated supply voltage	12...48 V AC 50/60 Hz 12...48 V DC

### Complementary

Local signalling	LED yellow, service life 100000 h of constant lighting efficiency (consumption 0.3 W)
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside : ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Auxiliary connection terminal	Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> without cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> without cable end
Compatibility code	V

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % ( 55 °C )
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...100 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---