



Main

Range of product	NG125
Product or component type	Add-on residual current devices
Device short name	Vigi NG125
Poles description	3P
[In] rated current	125 A
Network type	AC
Earth-leakage sensitivity	1000 mA 300 mA 500 mA
Earth-leakage protection time delay	Adjustable instantaneous/selective
Earth-leakage protection class	Type A

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	230...415 V AC 50/60 Hz
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
Mounting support	35 mm symmetrical DIN rail
Electrical connection to mcb	By screws
9 mm pitches	11
Width	180 mm
Product weight	0.75 kg
Electrical durability	10000 cycles conforming to IEC 60947-2
Connections - terminals	Tunnel type terminals rigid wire(s) 16...70 mm ² max Tunnel type terminals flexible wire(s) 10...50 mm ² max
Wire stripping length	20 mm
Tightening torque	6 N.m
Product compatibility	Single terminal
Market segment	Small commercial

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60947-2
IP degree of protection	IP40 conforming to IEC 60947-2
Pollution degree	3 conforming to IEC 60947-2
Electromagnetic compatibility	8/20 μ s impulse withstand, 5000 A conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % (55 °C)
Operating altitude	2000 m

Contractual warranty

Warranty period	18 months
-----------------	-----------