



### Main

Range	Acti 9
Range of product	NG125
Product or component type	Fault contact
Device short name	SDV NF
Signal contacts composition	1 NC
[In] rated current	0.1...1 A at 250 V AC - 50/60 Hz
9 mm pitches	1

### Complementary

Range compatibility	Vigi NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Mounting mode	Plug-on
Mounting location	Upstream
Height	36 mm
Width	8.8 mm
Depth	34.64 mm
Electrical durability	10000 cycles
Connections - terminals	Plate terminal 2 cable(s) 2.5 mm <sup>2</sup> flexible Plate terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Plate terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> rigid Plate terminal 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible Plate terminal 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible with ferrule Plate terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	NG125
Market segment	Small commercial

### Environment

Pollution degree	3
Tropicalisation	2

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

### Contractual warranty

Warranty period	18 months
-----------------	-----------