



Main

Range	Acti 9
Range of product	NG125
Product or component type	Double OC or fault contact
Device short name	OF and OF or OF and SD
Signal contacts composition	2 C/O
9 mm pitches	1

Complementary

Range compatibility	Acti 9 NG125LMA Acti 9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Mounting mode	Fixed
Mounting support	DIN rail
Height	102.8 mm
Width	15.3 mm
Depth	75.5 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal 2 cable(s) 1.5 mm ² flexible Plate terminal 1 cable(s) 2.5 mm ² flexible Plate terminal 1 cable(s) 2.5 mm ² rigid Plate terminal 2 cable(s) 1.5 mm ² rigid
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	NG125

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Pollution degree	3 conforming to EN/IEC 60947-5-1

Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------
