



Overview

Model Name	APC DC RECTIFIER, 500 WATT, 54VDC, WIDE INPUT, FULL SIGNALS, BLACK
Standard Lead Time	Usually Ships within 4 Weeks
Product Distribution	Albania , Algeria , Andorra , Angola , Armenia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cambodia , Cameroon , Canada , Cayman Islands , Central African Republic , Chad , China , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guinea , Hungary , Iceland , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Mali , Malta , Mauritania , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , Niger , Nigeria , Norway , Oman , Pakistan , Poland , Portugal , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , United States , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

Communications & Management

Product Distribution	Output OK
Product Distribution	Output OK

Output

Output Power Capacity	500.0 Watts / 10.5 VA
Max Configurable Power (Watts)	0.0 Watts / 0.0 VA
Nominal Output Voltage	48
Output Voltage Note	48 - 58V operating voltage
Output Voltage Note	Floating
Output Voltage Note	Negative ground , Positive ground
Output Voltage Note	2.0 mV
Output Voltage Note	32.0 dBrnC
Output Voltage Note	50.0 mV p-p
Output Voltage Note	0.0 mV RMS
Protection Device 1 Quantity	0
Protection Device 2 Quantity	0
Protection Device 3 Quantity	0

Protection Device 3 Quantity	Hot plug blind mate rear connector
Protection Device 3 Quantity	0.0

Input

Nominal Input Voltage	100~~120~~208~~230V
Input Frequency	50/60 Hz
Input Connections	Hot plug blind mate rear connector
Input voltage range for main operations	88 - 264 V
Input Power Factor at Full Load	0.99
Maximum Input Current per phase	6.0
Input Overcurrent Protection	Integral fuse in each rectifier

Physical

Maximum Height	127.0 mm
Maximum Width	64.0 mm
Maximum Depth	237.0 mm
Rack Height	3 U
Net Weight	1.77 kg
Shipping Weight	2.23 kg
Shipping Height	234.0 mm
Shipping Width	140.0 mm
Shipping Depth	338.0 mm
Color	Grey
Units per Pallet	0.0

Conformance

Approvals	CE , CSA 22.2 No. 950 , EN 60950 , UL 1950
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
Other Environmental Compliance	China RoHS