



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Total number of 18 mm modules	24

Complementary

Number of ways	24 ways N + 3 L (balanced)
Poles configuration for 1 way	1 x 3P + N 1 x 3P 3 x 1P + N
Connection pitch	9 mm
Connector type	Tooth
Distance between way	54 mm
Marking	N L1 N L2 N L3
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A (40 °C)
[Ue] rated operational voltage	400 V AC Ph/Ph 230 V AC Ph/N
[Ui] rated insulation voltage	440 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	48
Width	432 mm
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 N40 Acti 9 DT40 Acti 9 DT40 Vigi Multi 9 N40 Vigi / N40 Vigi / Vigi TG40 / Vigi TG60

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60947-7 EN/IEC 60439-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7

Contractual warranty

Warranty period	18 months
-----------------	-----------