



### Main

Range of product	C60
Range	Multi 9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	1P + N
Number of protected poles	1
Neutral position	Left
[In] rated current	16 A at 30 °C
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity code	N
Breaking capacity	6000 A Icn conforming to EN 60898 - 230/400 V AC 50/60 Hz 20 kA Icu conforming to EN/IEC 60947-2 - 130 V AC 50/60 Hz 10 kA Icu conforming to EN/IEC 60947-2 - 230...240 V AC 50/60 Hz 15 kA Icu conforming to EN/IEC 60947-2 - 60 V DC 1P 3 kA Icu conforming to EN/IEC 60947-2 - 400...415 V AC 50/60 Hz
Suitability for isolation	Yes conforming to IEC 60947-2

### Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230...240 V AC 50/60 Hz 230/400 V AC 50/60 Hz 400...415 V AC 50/60 Hz 130 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	15 kA conforming to EN/IEC 60947-2 - 130 V AC 50/60 Hz 7.5 kA conforming to EN/IEC 60947-2 - 230...240 V AC 50/60 Hz 2.25 kA conforming to EN/IEC 60947-2 - 400...415 V AC 50/60 Hz 6000 A conforming to EN 60898 - 230/400 V AC 50/60 Hz
Limitation class	3 conforming to EN/IEC 60947-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	NO
Connection pitch	18 mm : Between phase and neutral
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	73 mm
Product weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals flexible wire(s) 16 mm <sup>2</sup> max Tunnel type terminals rigid wire(s) 25 mm <sup>2</sup> max
Tightening torque	2 N.m downside 2 N.m upside power circuit
Earth-leakage protection	Separate block
Product compatibility	C60 auxiliary C60 accessories
Compatibility code	C60

## Environment

Standards	EN/IEC 60947-2 EN 60898
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------