



### Main

Range of product	C60
Range	Multi 9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60B
Device application	Distribution
Poles description	4P
Number of protected poles	4
Neutral position	Left
[In] rated current	40 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity code	B
Breaking capacity	10000 A Icn conforming to IEC 60898 - 400 V AC 50/60 Hz 10 kA Icu conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz 15 kA Icu conforming to EN/IEC 60947-2 - 400...415 V AC 50/60 Hz 30 kA Icu conforming to EN/IEC 60947-2 - 230...240 V AC 50/60 Hz
Suitability for isolation	Yes conforming to IEC 60947-2

### Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230...240 V AC 50/60 Hz 400 V AC 50/60 Hz 400...415 V AC 50/60 Hz 440 V AC 50/60 Hz
Limitation class	3 conforming to IEC 60898
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	8

Height	81 mm
Width	72 mm
Depth	73 mm
Product weight	0.48 kg
Mechanical durability	20000 cycles
Earth-leakage protection	Separate block
Compatibility code	C60

## Environment

Standards	EN/IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m

## Contractual warranty

Warranty period	18 months
-----------------	-----------