



### Main

Range	Multi 9
Range of product	C120 C60 DPN ID IDPN
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	110...130 V DC 110...415 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	C60 IDPN C120 ID DPN C60CTRL

### Complementary

Range compatibility	Multi 9: Multi 9 C60 Multi 9: Multi 9 ID
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm 73.5 mm
Product weight	0.06 kg
Connections - terminals	Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible Clamp terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> rigid

Clamp terminal 2 cable(s) 1.5 mm<sup>2</sup> flexible with ferrule

Wire stripping length	9 mm
Tightening torque	1 N.m

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------