



Main

Range	Multi 9
Range of product	DPN C60 IDPN C120 ID
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
9 mm pitches	2
Product compatibility	DPN ID C120 N40 C60CTRL C60 IDPN

Complementary

Range compatibility	Multi 9: Multi 9 N40 Multi 9: Multi 9 C60 Multi 9: Multi 9 ID
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	73.5 mm 68 mm
Product weight	0.06 kg
Connections - terminals	Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 1 cable(s) 0.5...2.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	LCIE KEMA ASEFA ASTA
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------