



Main

Range	Multi 9
Range of product	DPN IDPN C60 C120 ID
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2
Product compatibility	C120 DPN C60 N40 C60CTRL ID IDPN

Complementary

Range compatibility	Multi 9: Multi 9 N40 Multi 9: Multi 9 ID Multi 9: Multi 9 C60 C60CTRL
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	73.5 mm 68 mm
Product weight	0.06 kg
Connections - terminals	Clamp terminal 2 cable(s) 1.5 mm ² flexible

Clamp terminal 1 cable(s) 0.5...2.5 mm² rigid
Clamp terminal 2 cable(s) 1.5 mm² flexible with ferrule

Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	KEMA LCIE ASTA ASEFA
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------