



### Main

Range	Multi 9
Range of product	IDPN C60 DPN C120 ID
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
9 mm pitches	2
Product compatibility	C120 N40 ID C60 C60CTRL DPN IDPN

### Complementary

Range compatibility	Multi 9: Multi 9 N40 Multi 9: Multi 9 C60 Multi 9: Multi 9 ID
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

26947

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASTA ASEFA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------