



Main

Range	Multi 9
Range of product	C120 C60 DPN IDPN
Product or component type	Undervoltage release
Device short name	MN
[Uc] control circuit voltage	115 V AC 400 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	C60 IDPN C120 DPN C60CTRL N40

Complementary

Range compatibility	Acti 9: Acti 9 iDPN Multi 9: Multi 9 N40 Multi 9: Multi 9 C60
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 2 cable(s) 1.5 mm ² rigid
Wire stripping length	9 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tightening torque	1 N.m
-------------------	-------

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available End of life manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------