



### Main

Range	Multi 9
Product or component type	Undervoltage release
Range of product	C120 IDPN DPN Multi 9 C60
Device short name	MN
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	DPN C60CTRL C120 N40 C60 IDPN

### Complementary

Range compatibility	Acti 9: Acti 9 iDPN Multi 9: Multi 9 N40 Multi 9: Multi 9 C60
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> rigid Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> rigid
Wire stripping length	9 mm

Tightening torque	1 N.m
-------------------	-------

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASTA ASEFA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">End of life manual</a>
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------