



Main

Range	Multi 9
Range of product	IDPN C60 ID DPN C120
Product or component type	Undervoltage release
Device short name	MNx
[Uc] control circuit voltage	400 V AC 50/60 Hz
Control type	With external feeding
9 mm pitches	2
Product compatibility	C120 DPN C60 IDPN N40 C60CTRL ID

Complementary

Range compatibility	Acti 9: Acti 9 iDPN Multi 9: Multi 9 N40 Multi 9: Multi 9 C60 Multi 9: Multi 9 ID
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm ² flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

26971

Environment

Standards	EN/IEC 60947-5-1
Product certifications	KEMA ASEFA LCIE ASTA
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------