



### Main

Range	Multi 9
Product or component type	Undervoltage release
Range of product	C60
Device short name	MN
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
Control type	Standard
9 mm pitches	2
Product compatibility	C60 UL489 DC C60 C60 UL1077 C60 UL489

### Complementary

Range compatibility	Multi 9: Multi 9 C60 Multi 9: Multi 9 C60H-DC
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> rigid Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> rigid
Wire stripping length	9 mm
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
Product certifications	KEMA ASTA LCIE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## ASEFA

Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------