## Product data sheet Characteristics

# 27108

# voltage release - MN - 24 V AC / 24 V DC





### Main

Multi 9
C60
Undervoltage release
MN
24 V AC 50/60 Hz 24 V DC
Standard
2
C60 UL489 DC C60 C60 UL489 C60 UL1077

## Complementary

Main			
Range	Multi 9		
Range of product	C60		
Product or component type	Undervoltage release		
Device short name	MN		
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC		
Control type	Standard		
9 mm pitches	2		
Product compatibility	C60 UL489 DC C60 C60 UL489 C60 UL1077		
Complementary	M #: 0 M #: 0 000		
Range compatibility	Multi 9: Multi 9 C60 Multi 9: Multi 9 C60H-DC		
Local signalling	Action indicator		
Mounting mode	Fixed		
Mounting support	35 mm symmetrical DIN rail		
Height	82.5 mm		
Width	18 mm		
Depth	68 mm		
Connections - terminals	Pad terminal 1 cable(s) 2.5 mm² flexible Pad terminal 1 cable(s) 2.5 mm² rigid Pad terminal 2 cable(s) 1.5 mm² flexible Pad terminal 2 cable(s) 1.5 mm² rigid		
Wire stripping length	9 mm		
Tightening torque	1 N.m		

## Environment

Standards	EN/IEC 60947-5-1			
Product certifications	KEMA ASEFA LCIE			
Tropicalisation	ASTA  2 conforming to EN/IEC 60947-5-1			
Relative humidity	95 % at 55 °C			
Ambient air temperature for operation	-2550 °C			
Ambient air temperature for storage	-4085 °C			

## Offer Sustainability

Sustainable offer status	Green Premium product		
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity		
	Schneider Electric declaration of conformity		
REACh	Reference not containing SVHC above the threshold		
	Reference not containing SVHC above the threshold		
Product environmental profile	Available		
Product end of life instructions	Need no specific recycling operations		

### Contractual warranty

Warranty period	18 months	