



Main

Range	Multi 9
Range of product	C60
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Ie] rated operational current	1 A at 277 V AC - 50/60 Hz 0.3 A at 110 V DC 0.3 A at 125 V DC 0.4 A at 120 V AC - 50/60 Hz 0.8 A at 240 V AC - 50/60 Hz
[Uc] control circuit voltage	110...130 V DC 110...277 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	C60 UL1077 C60 UL489 DC C60 UL489 C60

Complementary

Range compatibility	Multi 9: Multi 9 C60 Multi 9: Multi 9 C60H-DC
Impulse duration	8 ms
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Pad terminal 1 cable(s) 2.5 mm ² flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
-----------	------------------

UL 489

Product certifications	LCIE ASEFA KEMA ASTA
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------
