



### Main

Range of product	NG160 NG160NA
Range	Compact
Device short name	Vigi NG160
Product or component type	Earth leakage add-on block
Device application	Wiring
Range compatibility	Compact - Compact NG circuit breaker
Poles description	4P
Protected poles description	4t
[In] rated current	160 A
Earth-leakage add-on module name	MH
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable
[IΔn] residual earth-leakage sensitive adjustment	0.03...3 A
Residual earth-leakage time delay adjustment type	Adjustable
[Δt] residual earth-leakage time delay adjustment	0...150 ms

### Complementary

Network type	AC
Network frequency	50/60 Hz
Mounting support	DIN rail
Electrical connection to mcb	By screws
Cable entry	Top
Connections - terminals	Tunnel type terminals
Device location in system	Group incomer Outgoer
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	< 150 ms

Overvoltage category	Class II
Height	240 mm
Width	120 mm
Depth	82.5 mm
Product weight	2.9 kg
Product compatibility	Single terminal

## Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2
Product certifications	LCIE ASTA KEMA ASEFA

## Contractual warranty

Warranty period	18 months
-----------------	-----------