



### Main

Range	Compact
Range of product	INS40...160
Product name	Compact INS
Product or component type	Switch disconnector
Device short name	Compact INS125
Switch-disconnector name	Compact INS125
Poles description	4P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	125 A AC 50/60 Hz for 220/240 V in category AC-22A 125 A AC 50/60 Hz for 380/415 V in category AC-22A 125 A AC 50/60 Hz for 440/480 V in category AC-22A 125 A AC 50/60 Hz for 500 V in category AC-22A 125 A AC 50/60 Hz for 660/690 V in category AC-22A 125 A AC 50/60 Hz for 220/240 V in category AC-23A 125 A AC 50/60 Hz for 380/415 V in category AC-23A 125 A AC 50/60 Hz for 440/480 V in category AC-23A 125 A AC 50/60 Hz for 500 V in category AC-23A 80 A AC 50/60 Hz for 660/690 V in category AC-23A 125 A DC for 125 V in category DC-22A (2 poles in series) 125 A DC for 250 V in category DC-22A (4 poles in series) 125 A DC for 125 V in category DC-23A (2 poles in series) 125 A DC for 250 V in category DC-23A (4 poles in series)
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	125 A ( 60 °C )
[Icm] rated short-circuit making capacity	154 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 20 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

Control type	Rotary handle
Handle colour	Red
Mounting mode	Fixed
Mounting support	DIN rail Plate
Upside connection	Front
Downside connection	Front
Maximum power	37 kW AC 50/60 Hz for 220/240 V in category AC-23 55 kW AC 50/60 Hz for 380/415 V in category AC-23 55 kW AC 50/60 Hz for 440 V in category AC-23 75 kW AC 50/60 Hz for 500/525 V in category AC-23 75 kW AC 50/60 Hz for 660/690 V in category AC-23
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for lthe	260 mm x 160 mm x 55 mm
[Icw] rated short-time withstand current	0.01 kA ( 30 s ) conforming to IEC 60947-3 1.23 kA ( 20 s ) conforming to IEC 60947-3 3.175 kA ( 3 s ) conforming to IEC 60947-3 5.5 kA ( 1 s ) conforming to IEC 60947-3
Mechanical durability	15000 cycles
Electrical durability	1500 cycles for 220/240 V AC 50/60 Hz in category AC-22A 1500 cycles for 380/415 V AC 50/60 Hz in category AC-22A 1500 cycles for 440 V AC 50/60 Hz in category AC-22A 1500 cycles for 500 V AC 50/60 Hz in category AC-22A 1500 cycles for 690 V AC 50/60 Hz in category AC-22A 1500 cycles for 220/240 V AC 50/60 Hz in category AC-23A 1500 cycles for 380/415 V AC 50/60 Hz in category AC-23A 1500 cycles for 440 V AC 50/60 Hz in category AC-23A 1500 cycles for 500 V AC 50/60 Hz in category AC-23A 1500 cycles for 690 V AC 50/60 Hz in category AC-23A 1500 cycles for 250 V DC in category DC-22A (4 poles in series) 1500 cycles for 250 V DC in category DC-23A (4 poles in series)
Connection pitch	30 mm
Height	100 mm
Width	135 mm
Depth	62.5 mm
Product weight	0.9 kg
Compatibility code	INS125

## Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------