



### Main

Range	Compact
Range of product	NS100...250
Product or component type	Trip unit
Range compatibility	Compact NS100
Device application	Motor
Poles description	3P
Protected poles description	3t
Network type	AC
Network frequency	50/60 Hz
Trip unit name	STR22ME
Trip unit technology	Electronic
Trip unit rating	100 A 20 °C 90 A 70 °C 95 A 60 °C
Protection type	Overload protection (long time) Short time short-circuit protection

### Complementary

Long time pick-up adjustment type Ir	Adjustable 10 settings
Long time pick-up adjustment range	0.6...1 x Ir
Long time delay adjustment type	Fixed
[Tr] long-time delay adjustment range	120...320 s at 1.5 x Ir 4...10 s at 7.2 x Ir 6...15 s at 6 x Ir
Short-time pick-up adjustment type I <sub>sd</sub>	Fixed
[I <sub>sd</sub> ] short-time pick-up adjustment range	13 x Ir
Short-time delay adjustment type	Fixed
[T <sub>sd</sub> ] short-time delay adjustment range	0.01...0.06 s
[T <sub>sd</sub> ] short-time delay adjustment range	0.01...0.06 s
Instantaneous pick-up adjustment type I <sub>i</sub>	Fixed

---

Display type	LED
--------------	-----

---

## Environment

---

Standards	IEC 60947-2
Product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP40 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---