



### Main

Range of product	NR100...250 NS100...250
Range	Compact
Product or component type	Earth leakage add-on block
Device application	Wiring
Range compatibility	Compact - Compact NS circuit breaker Compact - Compact NR circuit breaker
Poles description	3P
Protected poles description	3t
[In] rated current	100 A 160 A
Earth-leakage add-on module name	ME
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Fixed
[IΔn] residual earth-leakage sensitive adjustment	0.3 A
Residual earth-leakage time delay adjustment type	Fixed
[Δt] residual earth-leakage time delay adjustment	0...40 ms

### Complementary

Network type	AC
Network frequency	50/60 Hz
Mounting support	DIN rail
Electrical connection to mcb	By screws
[Ue] rated operational voltage	220...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	< 40 ms
Overvoltage category	Class II
Height	105 mm
Width	236 mm

---

Depth	86 mm
Product weight	2.5 kg

---

### Environment

---

Electrical shock protection class	Class II
Standards	IEC 60947-2
Product certifications	ASEFA ASTA KEMA LCIE

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---