



Main

Range of product	NR100...250 NS100...250 NS100...250 DC NS125E NSF150...250
Range	Compact
Device short name	OF
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	Compact - Compact NS circuit breaker Compact - Compact NSF circuit breaker Compact - Compact NR circuit breaker
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	DC-12 : 6 A DC 24 V DC-12 : 0.6 A DC 110 V AC-12 : 6 A AC 50/60 Hz 110 V AC-12 : 6 A AC 50/60 Hz 220/240 V AC-12 : 6 A AC 50/60 Hz 24 V AC-12 : 6 A AC 50/60 Hz 380/440 V AC-12 : 6 A AC 50/60 Hz 48 V AC-12 : 6 A AC 50/60 Hz 480 V AC-12 : 6 A AC 50/60 Hz 660/690 V AC-15 : 0.1 A AC 50/60 Hz 660/690 V AC-15 : 1.5 A AC 50/60 Hz 480 V AC-15 : 2 A AC 50/60 Hz 380/440 V AC-15 : 4 A AC 50/60 Hz 220/240 V AC-15 : 5 A AC 50/60 Hz 110 V AC-15 : 6 A AC 50/60 Hz 24 V AC-15 : 6 A AC 50/60 Hz 48 V DC-12 : 0.3 A DC 250 V DC-12 : 2.5 A DC 48 V DC-14 : 0.03 A DC 250 V DC-14 : 0.05 A DC 110 V DC-14 : 0.2 A DC 48 V DC-14 : 1 A DC 24 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Minimum load	100 mA at 24 V
--------------	----------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
