



Main

Range	Compact
Range of product	INV320...630 NSX400...630 EasyPact CVS100...250 NSX100...250 INSJ400 INV100...250 NG160 NG160NA INV630b...2500 NR400...630 INS320...630 INS40...160 EasyPact CVS400...630 INS630b...2500 NR100...250 PowerPact multistandard NSC100 INS250 INSE80
Device short name	SDE SDV OF SD
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Compact Compact NSX Compact Compact NG Compact Compact NR EasyPact EasyPact CVS Compact Compact INS Compact Compact INSE Compact Compact INSJ Compact Compact INV
Offer type	C4 C5
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Low level
-------------------------	-----------

29452

Auxiliary contacts operation	Early-break Early-make
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	5 A
[I _e] rated operational current	Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 1 A network: DC at 24 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 250 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 2.5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 48 V Utilisation category DC-12 : 5 A network: DC at 24 V
Minimum load	1 mA at 4 V DC
Product compatibility	PowerPact J-Frame PowerPact H-Frame PowerPact L-Frame
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------