



Main

Range	PowerLogic
Range of product	PowerLogic
Product name	PowerLogic Enercept
Device short name	Enercept
Product or component type	Power meter
Device application	Power monitoring Sub billing
Variant	Basic
Power monitoring	Basic instrumentation
Type of measurement	Active power Active energy
[Us] rated supply voltage	208...480 V, AC, 50/60 Hz
Network frequency	60 Hz 50 Hz

Complementary

[In] rated current	100 A
Poles description	2P + N 1P + N 3P
Current transformer type	Split core balance
Analogue input type	Split core CT, 0...100 A
Measurement voltage	208...480 V
Number of inputs	0
Number of outputs	0
Measurement accuracy	+/- 1 % 10...100 %
Communication port protocol	Modbus RTU
Communication port support	RS485
Communication network type	Modbus RTU
Mounting mode	Direct

3020B012S

Environment

Ambient air temperature for operation	0...60 °C
Relative humidity	95 %
Product certifications	UL CUL
Width	31 mm (internal) 121 mm (external)
Depth	30 mm
Height	30 mm (internal) 100 mm (external)
Product weight	1 kg

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
------------------------	--

Contractual warranty

Warranty period	18 months
-----------------	-----------