



Main

Range	Compact
Range of product	NR100...250
Product or component type	Trip unit
Range compatibility	Compact NR100 Compact NR250
Device application	Distribution
Poles description	4P
Protected poles description	3t 3t + 1.6 N
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	STR22SE OSN
Trip unit technology	Electronic
Trip unit rating	144 A 70 °C 152 A 60 °C 160 A 20 °C
Protection type	Overload protection (long time) Short time short-circuit protection

Complementary

Long time pick-up adjustment type Ir	Adjustable 48 settings
Long time pick-up adjustment range	0.25...0.63 x In
Long time delay adjustment type	Fixed
[Tr] long-time delay adjustment range	90...180 s at 1.5 x Ir
Short-time pick-up adjustment type I _{sd}	Adjustable 8 settings
[I _{sd}] short-time pick-up adjustment range	2...10 x Ir
Short-time delay adjustment type	Fixed
[T _{sd}] short-time delay adjustment range	0.04...0.06 s
[T _{sd}] short-time delay adjustment range	0.04...0.06 s

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Instantaneous pick-up adjustment type li	Fixed
Display type	LED

Environment

Standards	IEC 60947-2
Product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP40 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------