



### Main

Range	Compact
Range of product	Compact NS100...630
Product or component type	Circuit breaker
Product name	Compact NS
Device short name	Compact NS160L
Circuit breaker name	Compact NS160L
Device application	Distribution
Poles description	4P
Protected poles description	4t 3t 3t + N/2
Neutral position	Left
Network type	DC AC
Network frequency	50/60 Hz
[In] rated current	150 A 65 °C 160 A 40 °C
[U <sub>i</sub> ] rated insulation voltage	750 V AC 50/60 Hz conforming to IEC 60947-2
[U <sub>imp</sub> ] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[U <sub>e</sub> ] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2 750 V DC conforming to IEC 60947-2
Breaking capacity code	L
Breaking capacity	130 kA I <sub>cu</sub> at 440 V AC 50/60 Hz conforming to IEC 60947-2 150 kA I <sub>cu</sub> at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 150 kA I <sub>cu</sub> at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA I <sub>cu</sub> at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 50 kA I <sub>cu</sub> at 525 V AC 50/60 Hz conforming to IEC 60947-2 70 kA I <sub>cu</sub> at 500 V AC 50/60 Hz conforming to IEC 60947-2 130 kA at 480 V AC 50/60 Hz conforming to NEMA AB1 HIC 200 kA at 240 V AC 50/60 Hz conforming to NEMA AB1 HIC 50 kA at 600 V AC 50/60 Hz conforming to NEMA AB1 HIC
[I <sub>cs</sub> ] rated service breaking capacity	I <sub>cs</sub> 130 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 I <sub>cs</sub> 150 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2 I <sub>cs</sub> 150 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2 I <sub>cs</sub> 20 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2 I <sub>cs</sub> 50 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 I <sub>cs</sub> 70 kA 500 V AC 50/60 Hz conforming to IEC 60947-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A
Trip unit name	STR22SE
Trip unit technology	Electronic
Trip unit rating	144 A ( 70 °C ) 152 A ( 60 °C ) 160 A ( 20 °C )
Protection type	Overload protection (long time) Short time short-circuit protection Instantaneous short-circuit protection Protection of the fourth pole
Pollution degree	3 conforming to IEC 60947

## Complementary

Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Mechanical durability	40000 cycles
Electrical durability	20000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2 40000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2
Connection pitch	35 mm
Local signalling	Positive contact indication
Neutral protection setting	1 x Ir No protection 0.5 x Ir
Long time pick-up adjustment type Ir	Adjustable 48 settings
Long time pick-up adjustment range	0.4...1 x In
Long time delay adjustment type	Fixed
[Tr] long-time delay adjustment range	90...180 s 1.5 x Ir 3.2...5 s 7.2 x Ir 5...7.5 s 6 x Ir
Short-time pick-up adjustment type I <sub>sd</sub>	Adjustable 8 settings
[I <sub>sd</sub> ] short-time pick-up adjustment range	2...10 x Ir
Short-time delay adjustment type	Fixed
[T <sub>sd</sub> ] short-time delay adjustment range	0.04...0.06 s
Instantaneous pick-up adjustment type I <sub>li</sub>	Fixed
Instantaneous pick-up adjustment range	>= 11 x In
Display type	LED
Height	161 mm
Width	140 mm
Depth	86 mm
Compatibility code	NS160

## Environment

Standards	IEC 60947-2
Product certifications	ASEFA KEMA ASTA LCIE
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

---

Ambient air temperature for operation -25...70 °C

---

Ambient air temperature for storage -50...85 °C

---

### Contractual warranty

---

Warranty period 18 months

---

Product Life Status

**END-OF-SALE NOTICE**

30820