



Main

Range	Compact
Range of product	INS250
Product or component type	Switch disconnector
Product name	Compact INS
Device short name	Interpact INS250
Switch-disconnector name	Interpact INS250
Poles description	4P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-23A : 250 A AC 50/60 Hz 220/240 V DC-22A : 250 A DC 250 V 4 poles in series AC-22A : 250 A AC 50/60 Hz 440/480 V AC-23A : 250 A AC 50/60 Hz 500/525 V AC-22A : 250 A AC 50/60 Hz 220/240 V AC-22A : 250 A AC 50/60 Hz 500/525 V AC-23A : 250 A AC 50/60 Hz 380/415 V AC-22A : 250 A AC 50/60 Hz 380/415 V DC-22A : 250 A DC 125 V 2 poles in series AC-23A : 250 A AC 50/60 Hz 480 V NEMA AC-22A : 250 A AC 50/60 Hz 480 V NEMA AC-23A : 250 A AC 50/60 Hz 440/480 V DC-23A : 250 A DC 250 V 4 poles in series DC-23A : 250 A DC 125 V 2 poles in series AC-23A : 250 A AC 50/60 Hz 660/690 V AC-22A : 250 A AC 50/60 Hz 660/690 V
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Ith] conventional free air thermal current	250 A (60 °C)
[Icm] rated short-circuit making capacity	30 kA 690 V AC 50/60 Hz switch-disconnector alone 330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Control type	Red and yellow rotary handle
Handle colour	Red
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 : 150 kW 480 V NEMA AC 50/60 Hz AC-23 : 132 kW 380/415 V AC 50/60 Hz AC-23 : 75 kW 230 V NEMA AC 50/60 Hz AC-23 : 75 kW 220/240 V AC 50/60 Hz AC-23 : 150 kW 440 V AC 50/60 Hz AC-23 : 160 kW 500/525 V AC 50/60 Hz AC-23 : 210 kW 660/690 V AC 50/60 Hz
Rated duty	Uninterrupted
[I _{cw}] rated short-time withstand current	1.8 kA (30 s) conforming to IEC 60947-3 2.2 kA (20 s) conforming to IEC 60947-3 4.9 kA (3 s) conforming to IEC 60947-3 8.5 kA (1 s) conforming to IEC 60947-3
Mechanical durability	15000 cycles
Electrical durability	AC-22A : 1500 cycles 440 V AC 50/60 Hz AC-22A : 1500 cycles 500 V AC 50/60 Hz AC-22A : 1500 cycles 690 V AC 50/60 Hz AC-23A : 1500 cycles 440 V AC 50/60 Hz AC-23A : 1500 cycles 500 V AC 50/60 Hz AC-23A : 1500 cycles 690 V AC 50/60 Hz DC-22A : 1500 cycles 250 V DC 4 poles in series DC-23A : 1500 cycles 250 V DC 4 poles in series
Connection pitch	35 mm
Height	136 mm
Width	140 mm
Depth	96 mm
Product weight	2.2 kg
Compatibility code	INS250

Environment

Standards	IEC 60947-3 IEC 60947-1
Product certifications	KEMA-KEUR CCC
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------