



### Main

Range	Compact
Range of product	INS320...630
Product or component type	Switch disconnector
Product name	Compact INS
Device short name	Interpact INS500
Switch-disconnector name	Interpact INS500
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-22A : 500 A AC 50/60 Hz 220/240 V DC-22A : 500 A DC 125 V 2 poles in series AC-22A : 500 A AC 50/60 Hz 380/415 V AC-23A : 500 A AC 50/60 Hz 220/240 V AC-23A : 500 A AC 50/60 Hz 660/690 V AC-22A : 500 A AC 50/60 Hz 480 V NEMA AC-23A : 500 A AC 50/60 Hz 380/415 V DC-23A : 500 A DC 125 V 2 poles in series AC-22A : 500 A AC 50/60 Hz 660/690 V AC-22A : 500 A AC 50/60 Hz 440/480 V AC-23A : 500 A AC 50/60 Hz 440/480 V AC-22A : 500 A AC 50/60 Hz 500/525 V AC-23A : 500 A AC 50/60 Hz 500/525 V AC-23A : 500 A AC 50/60 Hz 480 V NEMA
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV 8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	500 A ( 60 °C )
[Icm] rated short-circuit making capacity	330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 50 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

Control type	Red and yellow rotary handle
Handle colour	Red
Mounting mode	Fixed
Mounting support	Rail Plate
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 : 355 kW 500/525 V AC 50/60 Hz AC-23 : 250 kW 440 V AC 50/60 Hz AC-23 : 132 kW 220/240 V AC 50/60 Hz AC-23 : 150 kW 230 V NEMA AC 50/60 Hz AC-23 : 250 kW 380/415 V AC 50/60 Hz AC-23 : 250 kW 480 V NEMA AC 50/60 Hz AC-23 : 500 kW 660/690 V AC 50/60 Hz
Rated duty	Uninterrupted
[I <sub>cw</sub> ] rated short-time withstand current	11.5 kA ( 3 s ) conforming to IEC 60947-3 20 kA ( 1 s ) conforming to IEC 60947-3 4 kA ( 30 s ) conforming to IEC 60947-3 4.9 kA ( 20 s ) conforming to IEC 60947-3
Mechanical durability	10000 cycles
Electrical durability	AC-22A : 1500 cycles 440 V AC 50/60 Hz AC-22A : 1500 cycles 500 V AC 50/60 Hz AC-22A : 1500 cycles 690 V AC 50/60 Hz AC-23A : 1500 cycles 440 V AC 50/60 Hz AC-23A : 1500 cycles 500 V AC 50/60 Hz AC-23A : 1500 cycles 690 V AC 50/60 Hz DC-23A : 1000 cycles 125 V DC
Connection pitch	45 mm
Height	205 mm
Width	185 mm
Depth	130 mm
Product weight	4.6 kg
Compatibility code	INS500

## Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------