



Main

Range	Compact
Range of product	INV320...630
Product name	Compact INV
Device short name	Interpact INV630
Switch-disconnector name	Interpact INV630
Poles description	4P
Network type	AC DC
Network frequency	50/60 Hz
Handle colour	Black
[I _e] rated operational current	AC-23A : 630 A AC 50/60 Hz 220/240 V AC-23A : 630 A AC 50/60 Hz 380/415 V AC-23A : 630 A AC 50/60 Hz 440/480 V AC-23A : 630 A AC 50/60 Hz 480 V NEMA AC-22A : 630 A AC 50/60 Hz 440/480 V DC-23B : 630 A DC 250 V 4 poles in series AC-23B : 630 A AC 50/60 Hz 380/415 V AC-23B : 630 A AC 50/60 Hz 220/240 V DC-21A : 550 A DC 125 V 2 poles in series AC-23A : 500 A AC 50/60 Hz 660/690 V DC-23A : 550 A DC 250 V 4 poles in series AC-22A : 630 A AC 50/60 Hz 220/240 V DC-22A : 550 A DC 125 V 2 poles in series AC-21A : 630 A AC 50/60 Hz 500/525 V AC-22A : 630 A AC 50/60 Hz 500/525 V AC-23B : 630 A AC 50/60 Hz 480 V NEMA AC-21A : 630 A AC 50/60 Hz 380/415 V AC-22A : 630 A AC 50/60 Hz 380/415 V AC-23B : 630 A AC 50/60 Hz 660/690 V AC-23A : 500 A AC 50/60 Hz 500/525 V DC-23A : 550 A DC 125 V 2 poles in series AC-22A : 630 A AC 50/60 Hz 480 V NEMA DC-22A : 550 A DC 250 V 4 poles in series AC-21A : 630 A AC 50/60 Hz 480 V NEMA AC-21A : 630 A AC 50/60 Hz 220/240 V AC-22A : 550 A AC 50/60 Hz 660/690 V AC-21A : 630 A AC 50/60 Hz 660/690 V AC-23B : 630 A AC 50/60 Hz 440/480 V DC-23B : 630 A DC 125 V 2 poles in series DC-21A : 550 A DC 250 V 4 poles in series AC-21A : 630 A AC 50/60 Hz 440/480 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

AC-23B : 630 A AC 50/60 Hz 500/525 V

[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	630 A (60 °C)
[Icm] rated short-circuit making capacity	330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 50 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	Yes
Pollution degree	3

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Rail Plate
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 : 200 kW 230 V NEMA AC 50/60 Hz AC-23 : 200 kW 220/240 V AC 50/60 Hz AC-23 : 315 kW 380/415 V AC 50/60 Hz AC-23 : 375 kW 480 V NEMA AC 50/60 Hz AC-23 : 400 kW 440 V AC 50/60 Hz AC-23 : 400 kW 500/525 V AC 50/60 Hz AC-23 : 560 kW 660/690 V AC 50/60 Hz
Rated duty	Uninterrupted
[Icw] rated short-time withstand current	11.5 kA (3 s) conforming to IEC 60947-3 20 kA (1 s) conforming to IEC 60947-3 4 kA (30 s) conforming to IEC 60947-3 4.9 kA (20 s) conforming to IEC 60947-3
Mechanical durability	10000 cycles
Electrical durability	DC-23A : 1000 cycles 250 V DC DC-23B : 200 cycles 250 V DC AC-21A : 1000 cycles 440 V AC 50/60 Hz AC-21A : 1000 cycles 500 V AC 50/60 Hz AC-21A : 1000 cycles 690 V AC 50/60 Hz AC-22A : 1000 cycles 440 V AC 50/60 Hz AC-22A : 1000 cycles 500 V AC 50/60 Hz AC-22A : 1000 cycles 690 V AC 50/60 Hz AC-23A : 1000 cycles 440 V AC 50/60 Hz AC-23A : 1000 cycles 500 V AC 50/60 Hz AC-23A : 1000 cycles 690 V AC 50/60 Hz AC-23B : 200 cycles 500 V AC 50/60 Hz AC-23B : 200 cycles 690 V AC 50/60 Hz DC-21A : 1000 cycles 250 V DC DC-22A : 1000 cycles 250 V DC
Connection pitch	45 mm
Height	205 mm
Width	185 mm
Depth	130 mm
Product weight	4.9 kg
Compatibility code	INV630

Environment

Standards	IEC 60947-3 IEC 60947-1
Product certifications	KEMA-KEUR CCC

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product identification

Product or component type	Switch disconnecter
---------------------------	---------------------

31175