



Main

Range	Compact
Range of product	INV320...630
Product name	Compact INV
Device short name	Interpact INV400
Switch-disconnector name	Interpact INV400
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
Handle colour	Red
[Ie] rated operational current	AC-23A : 400 A AC 50/60 Hz 500/525 V AC-22A : 400 A AC 50/60 Hz 500/525 V AC-22A : 400 A AC 50/60 Hz 380/415 V AC-23A : 400 A AC 50/60 Hz 660/690 V DC-23A : 400 A DC 125 V 2 poles in series AC-22A : 400 A AC 50/60 Hz 440/480 V AC-21A : 400 A AC 50/60 Hz 500/525 V AC-23A : 400 A AC 50/60 Hz 220/240 V AC-23A : 400 A AC 50/60 Hz 380/415 V AC-23A : 400 A AC 50/60 Hz 440/480 V AC-22A : 400 A AC 50/60 Hz 480 V NEMA AC-23A : 400 A AC 50/60 Hz 480 V NEMA AC-22A : 400 A AC 50/60 Hz 660/690 V AC-21A : 400 A AC 50/60 Hz 380/415 V DC-22A : 400 A DC 125 V 2 poles in series AC-22A : 400 A AC 50/60 Hz 220/240 V AC-21A : 400 A AC 50/60 Hz 480 V NEMA AC-21A : 400 A AC 50/60 Hz 660/690 V DC-21A : 400 A DC 125 V 2 poles in series AC-21A : 400 A AC 50/60 Hz 220/240 V AC-21A : 400 A AC 50/60 Hz 440/480 V
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	400 A (60 °C)
[Icm] rated short-circuit making capacity	330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 50 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	Yes
Pollution degree	3

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 : 200 kW 380/415 V AC 50/60 Hz AC-23 : 110 kW 230 V NEMA AC 50/60 Hz AC-23 : 110 kW 220/240 V AC 50/60 Hz AC-23 : 220 kW 440 V AC 50/60 Hz AC-23 : 220 kW 480 V NEMA AC 50/60 Hz AC-23 : 250 kW 500/525 V AC 50/60 Hz AC-23 : 400 kW 660/690 V AC 50/60 Hz
Rated duty	Uninterrupted
[I _{cw}] rated short-time withstand current	11.5 kA (3 s) conforming to IEC 60947-3 20 kA (1 s) conforming to IEC 60947-3 4 kA (30 s) conforming to IEC 60947-3 4.9 kA (20 s) conforming to IEC 60947-3
Mechanical durability	10000 cycles
Electrical durability	DC-23A : 1000 cycles 125 V DC AC-21A : 1000 cycles 440 V AC 50/60 Hz AC-21A : 1000 cycles 500 V AC 50/60 Hz AC-21A : 1000 cycles 690 V AC 50/60 Hz AC-22A : 1000 cycles 440 V AC 50/60 Hz AC-22A : 1000 cycles 500 V AC 50/60 Hz AC-22A : 1000 cycles 690 V AC 50/60 Hz AC-23A : 1000 cycles 440 V AC 50/60 Hz AC-23A : 1000 cycles 500 V AC 50/60 Hz AC-23A : 1000 cycles 690 V AC 50/60 Hz DC-21A : 1000 cycles 125 V DC DC-22A : 1000 cycles 125 V DC
Connection pitch	45 mm
Height	205 mm
Width	185 mm
Depth	130 mm
Product weight	4.6 kg
Compatibility code	INV400

Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	KEMA-KEUR CCC
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product identification

Product or component type

Switch disconnecter

31190