



Main

Range	Compact
Range of product	INS630b...2500
Product name	Compact INS
Device short name	Interpact INS630b
Product or component type	Switch disconnector
Switch-disconnector name	Interpact INS630b
Poles description	4P
Network type	DC AC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-23A : 630 A AC 50/60 Hz 220/240 V AC-23A : 630 A AC 50/60 Hz 380/415 V AC-23A : 630 A AC 50/60 Hz 440/480 V AC-23A : 630 A AC 50/60 Hz 500/525 V AC-23A : 630 A AC 50/60 Hz 660/690 V AC-23A : 630 A AC 50/60 Hz 480 V NEMA AC-22A : 630 A AC 50/60 Hz 660/690 V AC-22A : 630 A AC 50/60 Hz 440/480 V AC-22A : 630 A AC 50/60 Hz 220/240 V AC-21A : 630 A AC 50/60 Hz 500/525 V AC-22A : 630 A AC 50/60 Hz 500/525 V AC-21A : 630 A AC 50/60 Hz 380/415 V DC-21A : 630 A DC 125 V 2 poles in series AC-22A : 630 A AC 50/60 Hz 380/415 V DC-22A : 630 A DC 125 V 2 poles in series AC-22A : 630 A AC 50/60 Hz 480 V NEMA DC-23A : 630 A DC 125 V 2 poles in series AC-21A : 630 A AC 50/60 Hz 480 V NEMA AC-21A : 630 A AC 50/60 Hz 220/240 V DC-23A : 630 A DC 250 V 4 poles in series AC-21A : 630 A AC 50/60 Hz 660/690 V AC-21A : 630 A AC 50/60 Hz 440/480 V DC-21A : 630 A DC 250 V 4 poles in series DC-22A : 630 A DC 250 V 4 poles in series
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
[Ith] conventional free air thermal current	630 A ( 60 °C )

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Icm] rated short-circuit making capacity	330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 75 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

## Complementary

Control type	Direct front rotary handle
Handle colour	Black
Mounting mode	Fixed
Mounting support	Rail Plate
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 : 250 kW 220/240 V AC 50/60 Hz AC-23 : 710 kW 660/690 V AC 50/60 Hz AC-23 : 400 kW 380/400 V AC 50/60 Hz AC-23 : 560 kW 500/525 V AC 50/60 Hz AC-23 : 500 kW 415 V AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
[Icw] rated short-time withstand current	10 kA ( 20 s ) conforming to IEC 60947-3 20 kA ( 3 s ) conforming to IEC 60947-3 35 kA ( 1 s ) conforming to IEC 60947-3 42 kA ( 0.8 s ) conforming to IEC 60947-3 50 kA ( 0.5 s ) conforming to IEC 60947-3 8 kA ( 30 s ) conforming to IEC 60947-3
Mechanical durability	5000 cycles
Electrical durability	AC-23A : 1000 cycles 440/480 V AC 50/60 Hz DC-23A : 1000 cycles 125 V DC 2 poles in series DC-23A : 1000 cycles 250 V DC 4 poles in series AC-21A : 1000 cycles 220/240 V AC 50/60 Hz AC-21A : 1000 cycles 380/415 V AC 50/60 Hz AC-21A : 1000 cycles 440/480 V AC 50/60 Hz AC-21A : 1000 cycles 480 V AC 50/60 Hz conforming to NEMA AC-21A : 1000 cycles 500/525 V AC 50/60 Hz AC-21A : 1000 cycles 660/690 V AC 50/60 Hz AC-22A : 1000 cycles 220/240 V AC 50/60 Hz AC-22A : 1000 cycles 380/415 V AC 50/60 Hz AC-22A : 1000 cycles 440/480 V AC 50/60 Hz AC-22A : 1000 cycles 480 V AC 50/60 Hz conforming to NEMA AC-22A : 1000 cycles 500/525 V AC 50/60 Hz AC-22A : 1000 cycles 660/690 V AC 50/60 Hz AC-23A : 1000 cycles 220/240 V AC 50/60 Hz AC-23A : 1000 cycles 380/415 V AC 50/60 Hz AC-23A : 1000 cycles 480 V AC 50/60 Hz conforming to NEMA AC-23A : 1000 cycles 500/525 V AC 50/60 Hz AC-23A : 1000 cycles 660/690 V AC 50/60 Hz DC-21A : 1000 cycles 125 V DC 2 poles in series DC-21A : 1000 cycles 250 V DC 4 poles in series DC-22A : 1000 cycles 125 V DC 2 poles in series DC-22A : 1000 cycles 250 V DC 4 poles in series
Connection pitch	70 mm
Height	300 mm
Width	410 mm
Depth	146.5 mm
Product weight	18 kg
Compatibility code	INS630b

## Environment

Standards	IEC 60947-3 IEC 60947-1
Product certifications	KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------

31343