



Main

| | |
|---|--|
| Range | Compact |
| Range of product | Compact NS100...630 |
| Product or component type | Circuit breaker |
| Product name | Compact NS |
| Device short name | Compact NS250L |
| Circuit breaker name | Compact NS250L |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 3t 4t 3t + N/2 |
| Neutral position | Left |
| Network type | AC DC |
| Network frequency | 50/60 Hz |
| [In] rated current | 220 A 65 °C 250 A 40 °C |
| [U _i] rated insulation voltage | 750 V AC 50/60 Hz conforming to IEC 60947-2 |
| [U _{imp}] rated impulse withstand voltage | 8 kV conforming to IEC 60947-2 |
| [U _e] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 750 V DC conforming to IEC 60947-2 |
| Breaking capacity code | L |
| Breaking capacity | 130 kA I _{cu} at 440 V AC 50/60 Hz conforming to IEC 60947-2 150 kA I _{cu} at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 150 kA I _{cu} at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA I _{cu} at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 50 kA I _{cu} at 525 V AC 50/60 Hz conforming to IEC 60947-2 70 kA I _{cu} at 500 V AC 50/60 Hz conforming to IEC 60947-2 130 kA at 480 V AC 50/60 Hz conforming to NEMA AB1 HIC 200 kA at 240 V AC 50/60 Hz conforming to NEMA AB1 HIC 50 kA at 600 V AC 50/60 Hz conforming to NEMA AB1 HIC |
| [I _{cs}] rated service breaking capacity | I _{cs} 130 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 I _{cs} 150 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2 I _{cs} 150 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2 I _{cs} 20 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2 I _{cs} 50 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 I _{cs} 70 kA 500 V AC 50/60 Hz conforming to IEC 60947-2 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------|---|
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| Trip unit name | STR22SE |
| Trip unit technology | Electronic |
| Trip unit rating | 100 A (20 °C) 90 A (70 °C) 95 A (60 °C) |
| Protection type | Short time short-circuit protection Overload protection (long time) Instantaneous short-circuit protection Protection of the fourth pole |
| Pollution degree | 3 conforming to IEC 60947 |

Complementary

| | |
|--|--|
| Control type | Toggle |
| Mounting mode | Fixed |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Mechanical durability | 20000 cycles |
| Electrical durability | 10000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2 20000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2 |
| Connection pitch | 35 mm |
| Local signalling | Positive contact indication |
| Neutral protection setting | 0.5 x Ir 1 x Ir No protection |
| Long time pick-up adjustment type Ir | Adjustable 48 settings |
| Long time pick-up adjustment range | 0.4...1 x In |
| Long time delay adjustment type | Fixed |
| [Tr] long-time delay adjustment range | 90...180 s 1.5 x Ir 3.2...5 s 7.2 x Ir 5...7.5 s 6 x Ir |
| Short-time pick-up adjustment type I _{sd} | Adjustable 8 settings |
| [I _{sd}] short-time pick-up adjustment range | 2...10 x Ir |
| Short-time delay adjustment type | Fixed |
| [T _{sd}] short-time delay adjustment range | 0.04...0.06 s |
| Instantaneous pick-up adjustment type I _{li} | Fixed |
| Instantaneous pick-up adjustment range | >= 11 x In |
| Display type | LED |
| Height | 161 mm |
| Width | 140 mm |
| Depth | 86 mm |
| Compatibility code | NS250 |

Environment

| | |
|-------------------------|-------------------------------|
| Standards | IEC 60947-2 |
| Product certifications | KEMA ASTA LCIE ASEFA |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

31822