



Main

Range of product	NR400...630 NS400...630
Range	Compact
Product or component type	Earth leakage add-on block
Device application	Wiring
Range compatibility	Compact - Compact NS circuit breaker Compact - Compact NR circuit breaker
Poles description	4P
Protected poles description	4t
[In] rated current	400 A 630 A
Earth-leakage add-on module name	MB
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
[I Δ n] residual earth-leakage sensitive adjustment	0.3...30 A
Residual earth-leakage time delay adjustment type	Adjustable
[Δ t] residual earth-leakage time delay adjustment	150 ms 60 ms 0 ms 310 ms

Complementary

Network type	AC
Network frequency	50/60 Hz
Mounting support	DIN rail
Electrical connection to mcb	By screws
[U $_e$] rated operational voltage	220...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	< 800 ms
Overvoltage category	Class II
Height	180 mm

Width	355 mm
Depth	110 mm
Product weight	10.8 kg

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2
Product certifications	ASTA ASEFA KEMA LCIE

Contractual warranty

Warranty period	18 months
-----------------	-----------