



Main

Range of product	NS400...630
Range	Compact
Product name	Compact NS400 NA
Device short name	Compact NS400 NA
Product or component type	Switch disconnector
Device application	Distribution
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-23A : 400 A AC 50/60 Hz 1150 V
[Ui] rated insulation voltage	1250 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	400 A (60 °C)
[Ue] rated operational voltage	1150 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	NA
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	3 conforming to IEC 60947-3

Complementary

Control type	Toggle
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
Connection pitch	45 mm
Height	255 mm
Width	140 mm
Depth	110 mm
Product weight	5.2 kg

Environment

Standards	IEC 60947-3
Product certifications	ASTA KEMA ASEFA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------