



Main

Range of product	NS1600b...3200 NS630b...1600
Device short name	SD
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600
Offer type	C4 C5
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 480 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 4 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 48 V Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-12 : 6 A network: DC at 24 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 1 A network: DC at 24 V
Minimum load	100 mA at 24 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty period	18 months
-----------------	-----------
