



### Main

Range of product	NS630b...1600 NS1600b...3200
Device short name	SD
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600
Offer type	C4 C5
Signal contacts composition	1 NO/NC

### Complementary

Auxiliary contacts type	Low level
Mounting mode	Clip-on
[Ie] rated operational current	Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 250 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 2.5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 48 V Utilisation category DC-12 : 5 A network: DC at 24 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 24 V
Minimum load	1 mA at 4 V DC

### Contractual warranty

Warranty period	18 months
-----------------	-----------

33008